



Model 1000 Specifications

COMPACT CARPET and UPHOLSTERY CLEANER

Feature	English / Metric
Pump System	
Solution pump amps	1.25 A
Solution pump pressure	30 psi / 207 kPa
Solution pump voltage	120 V
Solution pump watts	150 watts
Vacuum System	
Airflow @ Orifice	80 cfm / 2.26 m ³ /h
Waterlift at sealed Orifice	71 in / 1805 mm
Vacuum motor type	Peripheral discharge, bypass; 4.8 in / 121 mm diameter; recognized by UL
Vacuum motor amps	7 A
Vacuum motor stages	2 stage
Vacuum motor voltage	120 V
Vacuum motor power	1.12 hp / 0.83 kW
Chassis & Body Construction	
Chassis & body construction	White, translucent, rotationally-molded polyethylene
Metal parts coating	White epoxy powder coating or zinc plating
Recovery System	
Recovery tank wet capacity	1.5 gallon / 5.67 liter
Vacuum hose length	8 ft / 2.43 m
Machine Dimensions	
Length	21 in / 535 mm
Machine Width	7.75 in / 195 mm
Height	17.5 in / 445 mm
Weight	18 lb / 8.2 kg
Solution Delivery System	
Solution capacity	2 gallon / 7.57 liter
Solution flow rate	0.25 gpm / 0.95 L/min
Solution hose description	Clear braided hose
Solution hose length	8 ft / 2.43 m
Solution pump watts	150 watts
Spray jets count	1 jet
Power Consumption	
Power consumption voltage	120 V
Power consumption watts	990 watts
Power consumption amps	8.25 amps
Power Cord	
Power cord length	25 ft / 7.62 m

重庆宇田丹增机电技术有限公司

重庆市渝北区加州花园A4-1-3

邮编：401147

联系方式：023-67627311 67627211

传真电话：023-67627311-801

Email: yutian@163.com

http://www.leiceo.com