

Click the model number below...

[1120 Specs](#) (base model)

[1140 Specs](#) (with heat)

[1160 Specs](#) (adjustable water pressure)

[1180 Specs](#) (heat and adjustable water pressure)



Model 1120 Specifications

PORTABLE CARPET EXTRACTOR

Feature	English / Metric
Vacuum Motor	
Airflow at 2-inch/ 50 mm orifice	101 cfm/ 2.8 m ³ /h
Waterlift at sealed orifice	137-inch/ 3480 mm
Vacuum motor type	Single speed, tangential discharge, 5.7-in/145 mm diameter, dual bell bearings, epoxy painted fan case; recognized by UL
Vacuum motor power	1.66 hp/ 1.23 kW
Vacuum motor stages	3 stage
Vacuum motor voltage	120 AC
Vacuum motor amps	13 A
Chassis/Body Construction	
Type	Rotationally-molded polyethylene
Caster diameter	4-inch/ 100 mm
Wheel diameter	12-inch/ 305 mm
Machine Dimensions	
Length	38-inch / 965 mm
Machine Width	19-inch / 480 mm
Height	38-inch / 965 mm
Weight	110 lb / 49.8 kg
Solution & Recovery System	
Solution tank capacity	15 gallon/ 56.7 liter
Recovery tank capacity	19 gallon/ 72 liter
Solution pump voltage	120 V
Solution pump amps	1 A
Solution pump open flow rate	1.8 gpm/ 6.81 liter/min
Power Cord	
Power cord length (1 cord)	25 ft/ 7.6 m
Power cord description	14 gauge 3 wire SJTO; recognized by UL/CSA, safety yellow, detachable
Sound Level	
Decibel rating at 10 ft/ 3 m	81 dBa
Decibel rating at 5 ft/ 1.5 m	82 dBa
Operator's ear	82 dBa
Warranty	3 YEARS/2500 HRS ON PARTS AND LABOR. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION.

重庆宇田丹增机电技术有限公司

重庆市渝北区加州花园A4-1-3

邮编：401147

联系方式：023-67627311 67627211

传真电话：023-67627311-801

Email:yutian@163.com

http://www.leiceo.com



Model 1140 Specifications

PORTABLE CARPET EXTRACTOR

Feature	English / Metric
Vacuum Motor	
Airflow at 2-inch/ 50 mm orifice	101 cfm/ 2.8 m ³ /h
Waterlift at sealed orifice	137-inch/ 3480 mm
Vacuum motor type	Single speed, tangential discharge, 5.7-in/145 mm diameter, dual bell bearings, epoxy painted fan case; recognized by UL
Vacuum motor power	1.66 hp/ 1.23 kW
Vacuum motor stages	3 stage
Vacuum motor voltage	120 AC
Vacuum motor amps	13 A
Chassis/Body Construction	
Type	Rotationally-molded polyethylene
Caster diameter	4-inch/ 100 mm
Wheel diameter	12-inch/ 305 mm
Machine Dimensions	
Length	38-inch / 965 mm
Machine Width	19-inch / 480 mm
Height	38-inch / 965 mm
Weight	135 lb / 61.2 kg
Solution & Recovery System	
Solution tank capacity	15 gallon/ 56.7 liter
Recovery tank capacity	19 gallon/ 72 liter
Solution pump voltage	120 V
Solution pump amps	1 A
Solution pump open flow rate	1.8 gpm/ 6.81 liter/min
Power Cord	
Power cord length (2 cords)	25 ft/ 7.6 m
Power cord description	14 gauge 3 wire SJTO; recognized by UL/CSA, safety yellow, detachable
Heat Exchanger	
Heat exchanger description	Cast aluminum, hairpin element cast into aluminum, surface mount thermostat; preset to 170°F (76.6° C) for safety
Sound Level	
Decibel rating at 10 ft/ 3 m	81 dBa
Decibel rating at 5 ft/ 1.5 m	82 dBa
Operator's ear	82 dBa
Warranty	3 YEARS/2500 HRS ON PARTS AND LABOR. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION.

重庆宇田丹增机电技术有限公司

重庆市渝北区加州花园A4-1-3

邮编：401147

联系方式：023-67627311 67627211

传真电话：023-67627311-801

Email: yutian@163.com

http://www.leiceo.com



Model 1160 Specifications

PORTABLE CARPET EXTRACTOR

Feature	English / Metric
Vacuum Motor	
Airflow at 2-inch/ 50 mm orifice	92 cfm/ 2.6 m ³ /h
Waterlift at sealed orifice	134-inch/ 3405 mm
Vacuum motor type	Single speed, tangential discharge, 7.2-in/180 mm diameter, dual bell bearings, epoxy painted fan case; recognized by UL
Vacuum motor power	2.5 hp/ 1.86 kW
Vacuum motor stages	3 stage
Vacuum motor voltage	120 AC
Vacuum motor amps	10 A
Chassis/Body Construction	
Type	Rotationally-molded polyethylene
Caster diameter	4-inch/ 100 mm
Wheel diameter	12-inch/ 305 mm
Machine Dimensions	
Length	38-inch / 965 mm
Machine Width	19-inch / 480 mm
Height	38-inch / 965 mm
Weight	130 lb / 58.9 kg
Solution & Recovery System	
Solution tank capacity	15 gallon/ 56.7 liter
Recovery tank capacity	19 gallon/ 72 liter
Solution pump voltage	120 V
Solution pump amps	5 A
Solution pump open flow rate	2.4 gpm/ 9 liter/min
Power Cord	
Power cord length	25 ft/ 7.6 m
Power cord description	14 gauge 3 wire SJTO; recognized by UL/CSA, safety yellow, detachable
Sound Level	
Decibel rating at 10 ft/ 3 m	78 dBa
Decibel rating at 5 ft/ 1.5 m	81 dBa
Operator's ear	81 dBa
Warranty	3 YEARS/2500 HRS ON PARTS AND LABOR. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION.

重庆宇田丹增机电技术有限公司

重庆市渝北区加州花园A4-1-3

邮编：401147

联系方式：023-67627311 67627211

传真电话：023-67627311-801

Email:yutian@163.com

http://www.leiceo.com



Model 1180 Specifications

PORTABLE CARPET EXTRACTOR

Feature	English / Metric
Vacuum Motor	
Airflow at 2-inch/ 50 mm orifice	92 cfm/ 2.6 m ³ /h
Waterlift at sealed orifice	134-inch/ 3405 mm
Vacuum motor type	Single speed, tangential discharge, 7.2-in/180 mm diameter, dual bell bearings, epoxy painted fan case; recognized by UL
Vacuum motor power	2.5 hp/ 1.86 kW
Vacuum motor stages	3 stage
Vacuum motor voltage	120 AC
Vacuum motor amps	10 A
Chassis/Body Construction	
Type	Rotationally-molded polyethylene
Caster diameter	4-inch/ 100 mm
Wheel diameter	12-inch/ 305 mm
Machine Dimensions	
Length	38-inch / 965 mm
Machine Width	19-inch / 480 mm
Height	38-inch / 965 mm
Weight	145 lb / 65.7 kg
Solution & Recovery System	
Solution tank capacity	15 gallon/ 56.7 liter
Recovery tank capacity	19 gallon/ 72 liter
Solution pump voltage	120 V
Solution pump amps	5 A
Solution pump open flow rate	2.4 gpm/ 9 liter/min
Power Cord	
Power cord length	25 ft/ 7.6 m
Power cord description	14 gauge 3 wire SJTO; recognized by UL/CSA, safety yellow, detachable
Heat Exchanger	
Heat exchanger description	Cast aluminum, hairpin element cast into aluminum, surface mount thermostat; preset to 170°F (76.6° C) for safety
Sound Level	
Decibel rating at 10 ft/ 3 m	78 dBa
Decibel rating at 5 ft/ 1.5 m	81 dBa
Operator's ear	81 dBa
Warranty	3 YEARS/2500 HRS ON PARTS AND LABOR. 10 YEARS ON ROTATIONALLY-MOLDED POLYETHYLENE TANKS. NO TRAVEL. PLEASE CONTACT COMPANY FOR MORE WARRANTY INFORMATION.

重庆宇田丹增机电技术有限公司

重庆市渝北区加州花园A4-1-3

邮编：401147

联系方式：023-67627311 67627211

传真电话：023-67627311-801

Email: yutian@163.com

http://www.leiceo.com