



Tennant F-Series Specifications

F5 Floor Machines – Single Speed

Feature		Specifications	
Product Name		Tennant F5 – 17”	Tennant F5 – 20”
Model Number		US # 9001808/ Canadian # 9001808	US # 9001811/ Canadian # 9001811
Pad Drive System			
Brush rpm	175 rpm		
Motor Volts	120 V		
Motor HP	1.5 hp (1.12 kW)		
Motor Type	AC, 66 frame, heavy duty, circuit breaker protected; triple planetary; precision gear box, 10:1 gear ratio		
Motor Amps	12 A		
Motor Watts	1100 watts		
Construction			
Handle	Twist grip operation with safety lock		
Base/ Handle	Corrosion-proof rotationally-molded polyethylene		
Dimensions			
Product Height	48 in/ 121.92 cm		
Product Length	22.75 in / 57.79 cm	23.50 in/ 59.70 cm	
Product Weight	97 lb/ 44 kg	100 lb/ 45.36 kg	
Product Width	17 in/ 403 mm	20 in/ 510 mm	
Productivity			
Max. Coverage (per hour)	2000 ft ² / 185.8 m ²	3000 ft ² / 278.7 m ²	
Decibel Rating			
Rating at operator's position	70 dBa		
Power Cord			
Length	50 ft/ 15.24 m		
Power Cord Type	14 gauge, 3–wire, SJT		
Solution Delivery System (Optional)			
Tank Volume	3 gal/ 11.36 L		
Nominal Solution Flow Rate	.1 gpm/ .38 L/min		
Coverage Rate Per Tank	1000 sq ft (92.9 sq m) / tank	1500 sq ft (135.35 sq m) / tank	
Warranty	3 YEARS/ 3 YEARS PARTS AND LABOR 10 YEARS ROTATIONALLY-MOLDED POLYETHYLENE BODY PLEASE CONTACT TENNANT COMPANY FOR MORE INFORMATION		



Tennant F-Series Specifications

F10 Floor Machines – Dual Speed

Feature		Specifications	
Product Name		Tennant F10 – 17”	
Model Number		US # 9001876/ Canadian # 9001876	F10 – 20” US # 9001814/ Canadian # 9001814
Pad Drive System			
Brush rpm		330 rpm (buff); 185 rpm (scrub)	
Motor Volts		120 V	
Motor HP		1.5 hp (1.12 kW)	
Motor Type		Permanent magnet DC, 66 frame, dual speed, circuit breaker protected; triple planetary; precision gear box, 10:1 gear ratio	
Motor Amps		120 V	
Motor Watts		1100 watts	
Construction			
Handle		Twist grip operation with safety lock	
Base/ Handle		Corrosion-proof rotationally-molded polyethylene	
Dimensions			
Product Height		48 in/ 121.92 cm	
Product Length		22.75 in / 57.79 cm	23.50 in/ 59.70 cm
Product Weight		94 lb/ 42.64 kg	97 lb/ 44 kg
Product Width		17 in/ 403 mm	20 in/ 510 mm
Productivity			
Max. Coverage (per hour)		2000 ft ² / 185.8 m ²	3000 ft ² / 278.7 m ²
Decibel Rating			
Rating at operator's position		71 dBa	
Power Cord			
Length		50 ft/ 15.24 m	
Power Cord Type		14 gauge, 3-wire, SJT	
Solution Delivery System (Optional)			
Tank Volume		3 gal/ 11.36 L	
Nominal Solution Flow Rate		.1 gpm/ .38 L/min	
Coverage Rate Per Tank		1000 sq ft (92.9 sq m) / tank	1500 sq ft (135.35 sq m) / tank
Warranty	3 YEARS/ 3 YEARS PARTS AND LABOR 10 YEARS ROTATIONALLY-MOLDED POLYETHYLENE BODY PLEASE CONTACT TENNANT COMPANY FOR MORE INFORMATION		

重庆宇田丹增机电技术有限公司

重庆市渝北区加州花园A4-1-3

邮编：401147

联系方式：023-67627311 67627211

传真电话：023-67627311-801

Email:yutian@163.com

http://www.leiceo.com